



Ultra robust design



Simplified installation



Competitive lead time



Custom-made in North America



## Contact

recharge@bectrol.com

(450) 774-1330

4550 Beaudry Av., Saint-Hyacinthe, Qc, Can

WWW.BECTROL.COM

SWITCHBOARD

## VOLTLINE UP TO 1600 A

Switchboards that drive the future of electric mobility



Spec Sheet	VOLTLINE SERIES 1000
Electrical	
Voltage	600 / 347 Vac
Current	Up to 1600 Amp
Frequency rating	60 Hz
AC input connection	3-Phase / L1 / L2 / L3 / Neutral / GNG
Internal connection	Busbar
Voltage circuit	480 Vac / 208 Vac / 120 Vac
SCCR	50 kA
Breakers for EV chargers	Customizable
GFCI outlets	1
Physical Dimensions (HxLxP)	90,6" x 94,5" x 23,6" 2300mm x 2400mm x 600mm
Weight	1 500 lbs / 680 kg
Operating temperatures	-40°F to 104°F / -40°C to 40°C
Cooling	Heating & heat dissipation
Environment, Compliance & Safety	
Enclosure	NEMA 3R indoor/outdoor electrical cabinet
Material	Painted steel cabinet / Painted stainless base
Electrical code	Designed for NFPA70 / NEC2020
Certifications	SPE 1000 / UL in progress

Ethernet / Cellular modem

Edge®, Chrome OS®, Firefox®

Web based / Remote user interface

Average power / Voltage / Current / Accumulated energy each post / Harmonics

Interface & Monitoring (under development)

Remote connectivity

Transaction summary

User interface Web interface